STEP-3







NOW SLIGHTLY PULL OUT THE SIDE LOCK (P23) & SLOWLY BRING DOWN THE TABLE

STEP-4

REPEAT THE SAME FOR THE 2ND HALF OF THE TABLE AS IN STEP- 1, 2 & 3

STEP-5



ATTACH POSTS TO THE LEFT AND RIGHT SIDE OF THE TABLE.

STEP- 6



POSTS, FEED STRING THROUGH GROOVES.

PLACE NET ONTO

ADJUST TENSION OF THE NET WITH THE PLASTIC STRIP

STEP- 7 ADJUST THE HEIGHT REQUIRED WITH THE HELP OF LEVELLERS (P20) ATTACHED ON ALL 4 OUTER LEGS (P6).

YOUR TABLE IS NOW READY FOR PLAY STORING THE TABLE

STEP-1







PULL OUT THE SIDE LOCK (P23) TO LIFT THE TABLE ON THE WHEELS. MAKE SURE THAT LOCK (P22) IS LOCKED PROPERLY FOR STORAGE

STEP- 2 REPEAT THE SAME FOR THE 2ND HALF.

<u>Safety Instructions:</u> Children below 14 years should not assemble the table. When lowering each half of the table top, make sure that the outer legs P6 are pulled gently outwards from the underside of the table, so far as they can go. Failure to do this may result in injury or damage to the table. This table is suitable for indoor & outdoor use.

Make sure that the wheel brakes are off when moving the table and are on when the table is stored or in the play position. Always cover the table when it is not in use.



Fitness Outdoor Table Tennis Table Assembly Instructions









- 1. TABLE TOP 12MM WATERPROOF BOARD- 1525×1370×12MM 2 NOS.
- 2. END FRAME PIPE -1485×30×20MM 2 NOS.
- 3. SIDE FRAME PIPE 1330×30×20MM 4 NOS.
- 4. INNER FRAME PIPE -1200×30×20MM 2 NOS.
- 5. SMALL BACK SUPPORT PIPE-800×19MM SQ 4 NOS.
- 6. OUTER LEG 1090×720×25×15MM 2 NOS.
- 7. INNER LEG -1220×510×25×15MM 2 NOS.
- 8. LONG BRACE SUPPORT 665×25×6MM 4 NOS.
- 9. WHEEL ASSEMBLY- 510×260×30×20MM 4NOS. 10. SET OF 8 WHEELS - 50 MM WITH 2 LOCK WHEELS
- 11. BRACKETS FOR OUTER/INNER LEG 75×27MM 16 NOS.
- 12. BRACKETS FOR FRAME PIPE 32MM SQ 36 NOS.
- 13. LONG BACK SUPPORT PIPE 1310×19MM SQ 2NOS.
- 14. BOLTS FOR OUTER/INNER LEG 38×6MM 8 NOS.
- 15. BOLTS FOR LONG BRACE SUPPORT FIXED TO OUTER/INNER LEG - 32×6MM - 4 NOS / 38×6MM - 4 NOS.
- 16. BOLTS FOR SIDE LOCK ATTACHED TO OUTER LEG 50×6MM WITH NUT WASHER AND BHOGLI - 2NOS.

17. BOLTS FOR SIDE LOCK ATTACHED TO BRACKET - 38×6MM - 2 NOS.

P18

- 18. DOME NUT 10MM- 8 NOS.
- 19. OUTER CORNER 40MM 4 NOS.
- 20. LEVELLERS 25×15MM CAPSULE 4 NOS.
- 21. PLASTIC CAPS FOR INNER FRAME PIPE 20×30MM- 8 NOS.
- 22. CENTRE LOCK 2 NOS.
- 23. SIDE LOCK 2 NOS.
- 24. WHEEL ASSEMBLY CAP 25×15MM 8 NOS.
- 25. NET POST SET 1 NOS.
- 26. SPARE NET 1 NOS.
- 27. SCREW FOR BRACKETS ON TOP 6/95- 342 NOS.
- 28. SCREW FOR OUTER CORNER 8/13 CSK- 12 NOS.
- 29. BOLT TO ATTACH WHEEL ASSEMBLY (P9) WITH INNER LEG (P7) 32×6MM - 8 NOS.
- 30. SPANNER 7.5/6MM 2 NOS.




P-30 - 7.5/6 MM - QTY. - 2

P-9 - 510×260×30×20 MM - QTY. - 4

ADULT ASSEMBLY REQUIRED

PLEASE READ THE SAFETY INSTRUCTIONS AT THE BOTTOM OF PAGE- 4

STEP - 1









CAREFULLY LIFT THE TABLE TOP HALF TO ATTACH WHEEL ASSEMBLY (P9) WITH INNER LEG (P7) USING NUT & BOLT 32×6MM AND TIGHTEN IT WITH THE HELP OF TWO SPANNERS (P30).

STEP-2





SLIGHTLY PULL OUT THE OUTER LEGS(P6) & **PUSH OPEN** THE TABLE SLIGHTLY BY **OPENING CENTRE** LOCK (P22).

Page 2 Page 3